
Overview

Product information



Interface module-DM72-DBK-37-37-4Y-00A(H)-30040000034

D-SUB module,input/output module,with screw connector and D-SUB female connector,can be installed on DIN35 rail,37 positions

Product advantages

9digits to 50digits
1:1 connection
Screw connection

Product certification

Technical data

Product drawing

3D model

Dimension

width	90mm
Height	59mm
length	109mm

Environmental data

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage / transport)	-20 °C ... 50 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3

Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	2A
Signal points	37
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	D-SUB connection
Connection volume	1
Number of digits	37
spacing	2.77mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm² ... 2.5 mm²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	38
screw thread	M3

Hard wire cross section	1.0 mm² ... 2.5 mm²

Accessories

Business data

Order number	30040000034
Packing unit	2
Minimum order quantity	10
Products weight (without packaging)	170