## Overview

### Product information



# Relay Socket-DPKF-14A-E3-00A(H)-30020000050

DPKF Relay Socket, used for 4PDT relays, screw connections

### Product advantages

- ☑ Screw base relay socket
- ☑ Safe isolation between coil and contacts
- ☑ 10A ,4PDT
- ☑ Screw top anti touch cover

### Product certification

## Technical data

### Product drawing

### 3D model

### Dimension

| | |
|---|---|
| width | 31mm |
| length | 69.6mm |
| Depth including bracket | 29.2mm |

### Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -45℃～+85℃ |
| Ambient temperature (storage / transport) | -40℃~+85℃ |

### Technical data

| | |
|---|---|
| Rated voltage UN | 300V |

| | |
|---|---|
| Installation location | Arbitrary |
| Assembly instructions | DIN35 rail |
| Maximum allowable current | 10A |

Connection data 1

| | |
|---|---|
| Connection name | enter |
| Connection method | Screw connection |
| Stripping length | 7-8mm |
| screw thread | M3 |
| Cross section of flexible conductor | 0.5-2.5mm² |
| Connectable guide cross section AWG | 20-14AWG |

Connection data 2

| | |
|---|---|
| Connection name | Output |
| Stripping length | 7-8mm |
| Cross section of flexible conductor | 0.5-2.5mm² |
| Connectable guide cross section AWG | 20-14AWG |
| Connection method | Screw connection |

## Accessories

Accessory

| | |
|---|---|
| Function Module | DMD-L-6/24V-00A(H) |

## Business data

| | |
|---|---|
| Order number | 30020000050 |
| Packing unit | 20 SKT |
| Minimum order quantity | 20 SKT |

| | |
|---|---|
| Products weight (without packaging) | 45g |