
Overview

Product information



DG200D-A-04P-13-00Z(H)-12050000298

Transfer Type,Rated current:200A.Rated voltage：：600V,Cross section:2～3/0AWG， Pitch:27mm,Color:black,Contact surface: Ni

Product advantages

☑ Screw connection for worldwide use
☑ Barrier wiring structure，stable and reliable connecion
☑ High current eletrical connections at power end can be met

Product certification

Technical data

Product drawing

3D model

Overview

Connection method	screw connection

Connection capacity

AWG	2~3/0AWG
Torque	6.0N.m

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	200A

Rated current (D)	5A
Rated current (C)	200A

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Screwdriver	Phillips screwdriver
screw thread	M8
Pitch	27mm
Number of potentials	4
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	Nickel plating
Insulation Materials (main class)	PA66+GF
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Business data

Order number	12050000298
Packing unit	6
Minimum order quantity	/
Products weight (without packaging)	321