Overview

Product information



switching module-DM50-IDC-40-40-1I-00A(H)-30040000061

switching module,IDC stitching line,can be installed on DIN35 rail

Product advantages

Can realize 32-bit I/O signal switching, 4 groups of signal wiring is convenient and quick

Product certification

Technical data

Product drawing

3D model

Dimension

width	57mm
Height	44mm
length	81mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	32
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	40
spacing	2.54mm

Connection data 2

Connection name	On-site side
Connection meets standards	UL1059
Connection method	IDC connection
Connection volume	4
Number of digits	10

Accessories

Business data

Order number	30040000061

Packing unit	1
Minimum order quantity	10
Products weight (without packaging)	80