
DEGSON

Overview

Product information



5EDGKM-7.62-10010002950

Pluggable terminal blocks,Rated current:32A.Rated voltage（III/2）:400V,pitch:7.62mm,Color:green,Contact surface :Tin

Product advantages

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying parts can be installed
☑ Universal installation method, suitable for various situations

Product certification

c UL us

Technical data

Product drawing

3D model

Connection capacity

Conductor cross section solid	0.2~4mm²
Conductor cross section flexible	0.2~4.0mm²
AWG	28~10AWG
Torque	0.5N.m
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	300V

Rated current (B)	30A
Rated current (D)	10A
Rated current (C)	30A

Electrical parameters IEC

Rated voltage	400V
Rated current	32A
Rated voltage(III/2)	400V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	0°
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	7.62mm
Number of potentials	5
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	5EDG-PWI
Bridge	/
Marking strip	/
Others	/

Business data

Order number	10010002950
Packing unit	150
Minimum order quantity	30
Products weight (without packaging)	22.56