
Overview

Product information



Relay module-DM72-RMS-08-PN-1-4M-00A(H)-30030000098

Subminiature Relay Module,with 20P Horn connector,with relay Socket ,4 relays can be installed,with relay Socket,with indicator light,Tyco relay,PNP or NPN signal can be input (Please contact us for relay replacement)

Product advantages

☑ Each signal channel and power supply voltage have LED status indicators
☑ Pluggable small relay, with a set of normally open contacts, one-to-one output at the output
☑ Suitable for NPN, PNP controller
☑ Freewheeling diode for each signal path

Product certification

Technical data

Product drawing

3D model

Overview

Installation location	Arbitrary
Number of channels	8
Shell Insulation Materials	PVC/PA66
color	green

Dimension

width	90mm
Height	62.5mm
length	120mm

Enter technical data

Rated input voltage	24VDC
Input voltage range relative to UN	0.9....1.1
protected name	Polarity protection
Protection circuits/components	Polarity Protection Diode
Status display/channel	green

Export technical data

contact type	1NO
Maximum switching voltage	240VAC 30VDC
Limit continuous current	10A
Fault monitoring (open circuit/short circuit)	no

Output connection data

connection name	output
Connection method	screw connection
Stripping length	6-7mm
thread	M3
connection volume	8
number of digits	2
Hard conductor cross section	1.0 ... 2.5mm²
Flexible conductor cross section	1.0 ... 2.5mm²
Connectable guide cross section AWG	28...12AWG

Enter connection data

connection name	enter
Connection method	IDC/MIL connectors
connection volume	2
number of digits	44854

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Accessories

Accessories

Wire harness	DX213-1S-500-00A(H)

Business data

Order number	30030000098
Packing unit	2
Minimum order quantity	10
Products weight (without packaging)	300