Overview

Product information



Interface module-DT075-2-00A(H)-30040000074

Power module, power extension, with screw connector, can be installed on DIN35 rail

Product advantages

Power distribution
Screw connection

Product certification

Technical data

Product drawing

3D model

Dimension

width	57mm
Height	41.5mm
length	65.6mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	15A
Signal points	2
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	Screw connection
Connection volume	1
Number of digits	4
spacing	7.62mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm² ... 2.5 mm²
Connectable guide cross section AWG	26 -12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	2
Number of digits	6
screw thread	M3
Hard wire cross section	1.0 mm² ... 2.5 mm²

Accessories

Business data

Order number	30040000074
Packing unit	2
Minimum order quantity	10
Products weight (without packaging)	110