Overview

Product information

Interface module-DT082-00A(H)-30040000084

8 positions input module,I/O interface module,with indicator light,with screw connector,can access binary NPN signal,can be installed on DIN35 rail

Product advantages

Quick-plug wiring
Screw connection

Product certification

Technical data

Product drawing

3D model

Dimension

width	57mm
Height	47mm
length	65.5mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	8
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	10
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	7mm
Cross section of flexible conductor	0.5mm² ... 1.5 mm²
Connectable guide cross section AWG	28-16AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	8
Number of digits	2
screw thread	M2
Hard wire cross section	0.5mm² ... 1.5 mm²

Accessories

Accessories

Wire harness	DX211-1S-500-00A(H)

Business data

Order number	30040000084
Packing unit	1
Minimum order quantity	10
Products weight (without packaging)	60