
## Overview

### Product information



# DG208-5.0-10060000705

PCB spring terminal blocks,Rated current:9A.Rated voltage （III/2）:450V,pitch:5.0mm,Color:gray,Contact surface :Tin

### Product advantages

- ☑ PUSH-IN connection technology, fast wiring
- ☑ Different poles can be combined through the side lock
- ☑ Universal installation method to ensure a high degree of flexibility in device design

### Product certification

## Technical data

### Product drawing

### 3D model

### Processing notes

| | |
|---|---|
| Process | Wave soldering/manual soldering |

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.2~0.75mm² |
| Conductor cross section flexible | 0.2~0.75mm² |
| AWG | 20~16AWG |
| Strip length | 7mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |

| | |
|---|---|
| Rated current (B) | 7A |
| Rated current (D) | 7A |

Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 450V |
| Rated current | 9A |
| Rated voltage(III/2) | 450V |
| Rated power frequency voltage(1min) | 2.5KV |

Item properties

| | |
|---|---|
| Connection direction | 0° |
| Type of installation | PCB welding |
| Pin arrangement | Double-row of misalignment |
| Connection method | Push-in spring connection |
| Pitch | 5mm |
| Number of potentials | 3 |
| Pluggable or not | no |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact point metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | UL1059/IEC60998 |

### Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃(depending on derating curve) |

## Accessories

### Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

### Tool

| | |
|---|---|
| Operating tool | / |
| Screwdriver | / |

## Business data

| | |
|---|---|
| Order number | 10060000705 |
| Packing unit | 1045 |
| Minimum order quantity | 30 |
| Products weight (without packaging) | 2.94 |