
Overview

Product information



DG141V-2.54-10060000445

PCB spring terminal blocks,Rated current:6A.Rated voltage （III/2）:130V,pitch:2.54mm,Color:green,Contact surface :Tin

Product advantages

- ☑ PUSH-IN connection technology, fast wiring
- ☑ Different poles can be combined through the side lock
- ☑ Universal installation method to ensure a high degree of flexibility in device design

Product certification

Technical data

Product drawing

3D model

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

Conductor cross section solid	0.2~1.0mm²
Conductor cross section flexible	0.2~1.0mm²
AWG	24~20AWG
Strip length	11mm

Electrical parameters UL

Rated voltage (B)	150V
Rated voltage (C)	150V

Rated voltage (D)	150V
Rated current (B)	2A
Rated current (D)	2A
Rated current (C)	2A

Electrical parameters IEC

Rated voltage	130V
Rated current	6A
Rated voltage(III/2)	130V
Rated power frequency voltage(1min)	1.25KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Push-in spring connection
Pitch	2.54mm
Number of potentials	27
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10060000445
Packing unit	250
Minimum order quantity	30
Products weight (without packaging)	13.76