
Overview

Product information



DGBSC-SG01/4-10080000647

Building wiring terminals,Rated current:32A.Rated voltage （III/2）:450V,pitch:5.6mm,Color:transparent,Contact surface :Tin

Product advantages

☑ Rotatable operating handle,easy to operate
☑ Suitable for field wiring,saving installation time
☑Bio-based materials and post-consumer recycled materials to reduce carbon emissions

Product certification

Technical data

Product drawing

3D model

Connection capacity

Conductor cross section solid	0.2~4mm²
Conductor cross section flexible	0.2~4.0mm²
AWG	24~12AWG
Strip length	12mm

Electrical parameters UL

Rated voltage (B)	600V

Electrical parameters IEC

Rated voltage	450V

Rated current	32A
Rated voltage(III/2)	450V

Item properties

Connection method	Push-in spring connection
Pitch	5.6mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)	-40℃~85℃(depending on derating curve)

Accessories

Accessories

Install accessories	DGBSC-ACC01
Protective board	DGBSC-ACC05

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10080000647
Packing unit	100
Minimum order quantity	
Products weight (without packaging)	3.234