
DEGSON

## Overview

### Product information



# 8EDGKG-7.62-10020002114

Pluggable terminal blocks,Rated current:20A.Rated voltage（III/3）:400V,pitch:7.62mm,Color:gray,Contact surface :Tin

### Product advantages

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Cage clamp connection technology,fast wiring
☑ Universal installation method, suitable for various situations

### Product certification

## Technical data

### Product drawing

### 3D model

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.2~2.5mm² |
| Conductor cross section flexible | 0.2~2.5mm² |
| AWG | 22~14AWG |
| Strip length | 10mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (C) | 300V |
| Rated current (B) | 15A |
| Rated current (C) | 15A |

## Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 400V |
| Rated voltage(III/3) | 400V |
| Rated current | 20A |
| Rated surge voltage(III/3) | 4KV |

## Item properties

| | |
|---|---|
| Connection direction | 0° |
| Connection method | spring-cage connection |
| Pitch | 7.62mm |
| Number of potentials | 6 |
| Pluggable or not | Yes |
| Number of rows | 1 |

## Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact point metal surface | tin-plated |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

## Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

## Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃(depending on derating curve) |

## Accessories

### Tool

| | |
|---|---|
| Screwdriver | / |
| Operating tool | DG010 |

### Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | DG018-7.5 |
| Marking strip | / |
| Others | DG017 |

## Business data

| | |
|---|---|
| Order number | 10020002114 |
| Packing unit | 165 |
| Minimum order quantity | 30 |
| Products weight (without packaging) | 14.2 |