
Overview

Product information



DG250-A-12010001128

Up and down transfer terminal，Rated current：200A，Rated voltage（UL)：1000V，Croos section：6~250kcmil，Pitch：27mm，Color：black，contact surface：Ni

Product advantages

☑ Screw connection for worldwide use
☑ Fence type wiring structure，stable and reliable connecion
☑ High current eletrical connections at power end can be met

Product certification

CE

Technical data

Product drawing

3D model

Signal feedback

HVIL	Yes

Electrical parameters UL

Rated voltage	1000V

Connection capacity

AWG	6~250kcmil
Torque	6.0N.m

Item properties

Connection direction	90°

Type of installation	panel
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M8
Pitch	27mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059

Environmental data

Ambient temperature (operation)	-40℃~120℃(depending on derating curve)

Accessories

Business data

Order number	12010001128
Packing unit	8
Minimum order quantity	8

Products weight (without packaging)	2500