
DEGSON

## Overview

### Product information



# 8EDGK-3.81-10020002060

Pluggable terminal blocks,Rated current:10A.Rated voltage （III/3）:130V,pitch:3.81mm,Color:gray,Contact surface :Tin

### Product advantages

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Cage clamp connection technology,fast wiring
☑ Universal installation method, suitable for various situations

### Product certification

c UL us

VDE

## Technical data

### Product drawing

### 3D model

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.2~1.5mm² |
| Conductor cross section flexible | 0.2~1.5mm² |
| AWG | 28~14AWG |
| Strip length | 6mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 10A |
| Rated current (D) | 10A |

## Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 130V |
| Rated voltage(III/3) | 130V |
| Rated current | 10A |
| Rated surge voltage(III/3) | 2.5KV |

## Item properties

| | |
|---|---|
| Connection direction | 0° |
| Connection method | spring-cage connection |
| Pitch | 3.81mm |
| Number of potentials | 15 |
| Pluggable or not | Yes |
| Number of rows | 1 |

## Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact point metal surface | tin-plated |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

## Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

## Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃(depending on derating curve) |

## Accessories

### Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

### Tool

| | |
|---|---|
| Operating tool | / |
| Screwdriver | / |

## Business data

| | |
|---|---|
| Order number | 10020002060 |
| Packing unit | 240 |
| Minimum order quantity | 30 |
| Products weight (without packaging) | 11.86 |