Overview

Product information

DSKK2.5/2P-PV-11040001048

Plug-in guide rail terminal, wiring method: plug-in/straight insertion connection, connection quantity: 2, digit: 1, wiring capacity: 0.2 mm² - 6 mm², AWG: 24 - 10, width: 6.2 mm, color: yellow-green, installation method: NS35/7.5, NS35/15 Sensor terminals, wiring method: Direct insertion connection, rated voltage: 250 V, rated current: 13.5 A, connection quantity: 4, digit: 1, wiring capacity: 0.14 mm² - 1.5 mm², AWG: 26 - 14, width: 3.5 mm, color: gray, installation method: NS35/7.5, NS35/15

Product advantages

☑ Direct insertion connection technology, tool free operation, more convenient and efficient; ☑ Equipped with an orange pull button, the wire can be released with a Phillips or Phillips screwdriver; ☑ Dual channel bridging well, easy to achieve potential distribution; ☑ Unique plug-in bridge components with high circuit connection efficiency; ☑ Can match large-area identification and clear wiring; ☑ Equipped with test holes for easy circuit testing.

Product certification

Technical data

Product drawing

3D model

Overview

Connection method	Push in connection
Number of rows	2
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Insulating material group	I
standard test	IEC60947-7-1

Dimension

width	5.2mm
End plate width	1.5mm
NS 35/7,5 Height	50.75mm
NS 35/15 Height	58.25mm
length	73.5mm
high	43.25mm

Wiring data

Strip length	9~10mm
Conductor cross section solid AWG	26~12
Conductor cross section solid	0.14~4mm²
Conductor cross section flexible	0.14-4mm²
Conductor cross section flexible (ferrule without plastic sleeve)	0.14-4mm²
Conductor cross section flexible (ferrule with plastic sleeve)	0.14-4mm²

IEC Electrical parameters

Rated voltage (III / 3)	500V
Rated current (III / 3)	24A
Rated surge voltage	8KV

UL Electrical parameters

Rated voltage	300V
Rated current	20A

Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

Safety test

Anti-finger touch	Passed the test

Environmental protection

RoHS	No excessive harmful substances
REACh SVHC	Lead 7439-92-1

Accessories

logo

Top marker bar	ZS5/ZB5
Side marking strip	ZSF5/ZT5

Attachment

flat-head screwdriver	0.6x3.5
Bridge components	DFBXXX-5.2(XXX:2,3,4,5,6,7,8,9,10,20)
end plate	D-DSSKK2.5
flip cover	ATP-DS / ATP-PC N
partition	E-PC 1100A / E-WS N

install

terminal fixture	DLM2 / KLM3-20x8 / KLM3-44x8
Terminal strip marking bracket	NS35/7.5-1000-00A(H)

DIN rail	AP3-COVER / AP3-T / AP3-T-KS

Business data

Order number	11040001048
Packing unit	50
Minimum order quantity	50
Products weight (without packaging)	10.61g