
DEGSON

## Overview

### Product information



# 15EDGVH-2.5-10030004129

Pluggable terminal blocks,Rated current:4A.Rated voltage（Ⅱ/2）:100V,pitch:2.5mm,Color:green,Contact surface :Tin

### Product advantages

☑ Universal installation method to ensure a high degree of flexibility in device design
☑ Multi-layer wire connection can achieve higher contact density

### Product certification

c UL us

## Technical data

### Product drawing

### 3D model

### Processing notes

| | |
|---|---|
| Process | Wave soldering/manual soldering |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 150V |
| Rated current (B) | 5A |

### Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 100V |
| Rated current | 4A |
| Rated voltage(Ⅱ/2) | 100V |
| Rated surge voltage(Ⅱ/2) | 2.5KV |

## Item properties

| | |
|---|---|
| Connection direction | 90° |
| Type of installation | PCB welding |
| Pin arrangement | Double-row in a straight line |
| Pitch | 2.5mm |
| Number of potentials | 20 |
| Pluggable or not | Yes |
| Number of rows | 2 |

## Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

## Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

## Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃(depending on derating curve) |

# Accessories

## Tool

| | |
|---|---|
| Screwdriver | / |
| Operating tool | / |

## Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | 15EDG-PWI-2.5 |

## Business data

| | |
|---|---|
| Order number | 10030004129 |
| Packing unit | 350 |
| Minimum order quantity | 30 |
| Products weight (without packaging) | 6.85 |