
Overview

Product information



DG380-3.81-10040001350

PCB terminal blocks,Rated current:16A,Rated voltage （III/2）200V,Cross section:1.5mm²,pitch:3.81mm,connector method:Screw connector with tension sleeve,Color:green,Contact surface :Tin

Product advantages

☑ Fixed screw connection technology,safe and reliable
☑ Universal installation method to ensure a high degree of flexibility in device design

Product certification

Technical data

Product drawing

3D model

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

Conductor cross section solid	0.2~1.5mm²
Conductor cross section flexible	0.2~1.5mm²
AWG	30~14AWG
Torque	0.2N.m
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	12A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	200V
Rated voltage(III/3)	250V
Rated current	16A
Rated voltage(III/2)	200V
Rated voltage(II/2)	500V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2
Pitch	3.81mm
Number of potentials	9
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Accessories

Coding strip	/
Bridge	DG032-3.81
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	0.4x2.5mm，Slotted screwdriver

Business data

Order number	10040001350
Packing unit	360
Minimum order quantity	30

Products weight (without packaging)	5.46