
Overview

Product information



DG238-10.0-10060001829

PCB spring terminal blocks,Rated current:24A.Rated voltage（III/2）:450V,pitch:10.0mm,Color:White,Contact surface :Tin

Product advantages

☑ Multiple wiring holes for current distribution
☑ Panel mounting, suitable for various situations
☑ Can realize horizontal wire-to-wire connection

Product certification

Technical data

Product drawing

3D model

Connection capacity

AWG	22~14AWG
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	600V
Rated current (B)	20A

Electrical parameters IEC

Rated current	24A
Rated voltage(III/2)	450V

Rated power frequency voltage(1min)	2.5KV

Item properties

Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	4
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PA66
Insulating material group	Ⅰ
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10060001829
Packing unit	40
Minimum order quantity	30
Products weight (without packaging)	12.13