
Overview

Product information



2EDGKDRM-5.08-10020002029

Pluggable terminal blocks,Rated current:20A.Rated voltage（III/2）:320V,pitch:5.08mm,Color:green,Contact surface :Tin

Product advantages

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying requirements can be met
☑ Universal installation method, suitable for various situations

Product certification

Technical data

Product drawing

3D model

Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	26~12AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	10A

Electrical parameters IEC

Rated voltage	250V

Rated current	12A
Rated voltage(III/2)	250V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	0°
Connection method	Push-in spring connection
Pitch	5.08mm
Number of potentials	3
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10020002029
Packing unit	560
Minimum order quantity	30
Products weight (without packaging)	5.09