
Overview

Product information



15EDGVHDM-3.5-10030003440

Pluggable terminal blocks,Rated current:10A.Rated voltage （III/2）:125V,pitch:3.5mm,Color:green,Contact surface :Tin

Product advantages

☑ Universal installation method to ensure a high degree of flexibility in device design
☑ Multi-layer wire connection can achieve higher contact density

Product certification

Technical data

Product drawing

3D model

Processing notes

Process	Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	150V
Rated current (B)	10A
Rated current (C)	10A

Electrical parameters IEC

Rated voltage	250V
Rated voltage(III/3)	80V
Rated current	10A

Rated voltage(III/2)	125V
Rated voltage(II/2)	250V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Pitch	3.5mm
Number of potentials	8
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Tool

Bolt driver	/
Line taking tool	/

Enclosure

Code strip	17EDG-PWP
Bridge components	/
Marking bar	/
Else	/

Business data

Order number	10030003440
Packing unit	1080
Minimum order quantity	
Products weight (without packaging)	3.51