DEGSON

## Overview

### Product information



# DG30-A-12050000083

Transfer barrier terminal blocks,Rated current:30A.Rated voltage（UL）:300V,Cross section:28~10AWG,pitch:13.00mm,Color:black,Contact surface:Tin

### Product advantages

☑ Screw connection for worldwide use
☑ Fence type wiring structure, stable and reliable connection
☑ Panel mounting for electrical transfer between two devices in a small space

### Product certification

c UL us  CE

## Technical data

### Product drawing

### 3D model

### Connection capacity

| | |
|---|---|
| AWG | 28~10AWG |
| Torque | 1.2N.m |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 30A |
| Rated current (D) | 10A |

### Electrical parameters IEC

| | |
|---|---|
| | |

| | |
|---|---|
| Rated current | 41A |

### Item properties

| | |
|---|---|
| Type of installation | panel |
| Pin arrangement | Double-row in a straight line |
| Connection method | Screw connection |
| Screwdriver | slotted-phillips screwdriver |
| screw thread | M4 |
| Pitch | 13mm |
| Number of potentials | 10 |
| Pluggable or not | no |
| Number of rows | 2 |

### Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact point metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | II |
| Flammability rating | UL94V-0 |

### Mechanical tests

| | |
|---|---|
| Test Specification | UL1059 |

### Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~120℃(depending on derating curve) |

## Accessories

### Accessories

## Business data

| | |
|---|---|
| Order number | 12050000083 |
| Packing unit | 25 |
| Minimum order quantity | / |
| Products weight (without packaging) | 121 |