Überblick

Informationen zum Produkt



DSW-A6K2040P-30090000009

2 10/ 100/1000Mbs BaseXSFP slot(does not contain SFP optical module)+4802.3af/at PoE 10/ 100/1000Mbs BaseT ,1CLI management port .IP30,Operating temperature-40～75℃.MTBF≥400,000H.

Produktvorteile

☑Unmanaged Industrial Switch
☑2 100/1000BaseX SFP Ports(SFP module not included),4 802.3af/at PoE 10/100/1000BaseT Ports,1 Management Serial CLI Port
☑>IP40 Protection Class
☑Operating Temperature from －40°C to +75°C
☑MTBF over 400K hours
☑Dual 48－57VDC Power Inputs.

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

interface

Port 1 Type	RJ45
Number of ports 1	5
	2
Port 2 Type	SFP optical module
Transmission rate	10/100/1000 Mbps

Mechanical structure

Shell material	Die-cast aluminum alloy housing
Installation method	Card rail installation

Protection class	IP30

exchange property

MAC table size	4K
Bandwidth backplane	20Gbps
packet buffer	1.5Mb

MTBF

Standards compliant	Telcordia SR-332
operating hours	≥400,000H

Warranty

Warranty	5 years

Power over Ethernet (PoE)

PoE output standard 1	IEEE 802.3af
PoE output standard 2	IEEE 802.3at
PoE output power1	120W
PoE output power2	62.4W
PoE output current1	0.625A
PoE output current 2	0.325A

power supply

Supply voltage range	9.6~60VDC & 18~30VAC
reverse voltage protection	support
Connection Type	5P plug-in terminal
connecting wire diameter	0.5~1.5mm/ 28~16AWG
Overcurrent protection	support
Input voltage	48 - 57VDC redundant dual input

Dimension

high	140mm
length	110mm
width	52mm

Environmental data

working altitude	≤2000m
Operating temperature	-40°C~+75°C
storage temperature	-40°C~+85°C
humidity	5% ~ 95% (non-condensing)

Zubehör

SFP optical module

DSW-SFP-10-S-20	

Die Geschäftsdaten

Nummer der Bestellung	30090000009
Verpackung Einheit	1 STK
Minimale Bestellmenge	1 STK
Produktgewicht (ohne Verpackung)	600g