
## Przegląd

### Informacje o produkcie



# DS1.5-QU-PE-11040000076

Push-in Din-Rail TB, connector method: Push-in connector, Number of connectors: 4, Number of potentials: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Color: green-yellow, Mounting type: NS35/7.5, NS35/15

### Zalety produktu

☑Push-in connection technology, tool-free operation, more convenient and faster;
☑With orange wire button, one word or cross screwdriver can release wire.
☑Optional marker to avoid wire mis-inserting.
☑Equipped with test holes for easy testing of the circuit.

### Certyfikacja produktu

## Dane techniczne

### Rysunek produktu

### Model 3D

### Wiring data

| | |
|---|---|
| Strip length | 8~10mm |
| Conductor cross section solid | 0.14~1.5mm² |
| Conductor cross section flexible | 0.14~1.5 mm² |
| Conductor cross section solid AWG | 26~14 |

### Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |

### IEC Electrical parameters

| | |
|---|---|
| Rated surge voltage | 6KV |

### Environmental protection

| | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

### Dimension

| | |
|---|---|
| NS 35/7,5 Height | 32.1mm |
| End plate width | 1.5mm |
| NS 35/15 Height | 39.6mm |
| length | 63.2mm |
| width | 3.5mm |

### Overview

| | |
|---|---|
| Connection type | In line connection |
| Number of rows | 1 |
| number of connections | 4 |
| Open-end side panels | Yes |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

## Akcesoria

### Marker

| | |
|---|---|
| Top marker | ZB3.5 / ZS3.5 |
| Side marker | ZSF3.5 |
| Marker support | DTH3.5-25x3.5 / DTH3.5-25x12 |

### Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) mm | 0.4x2.5 |
| Bridge | / |
| End cover | D-DS1.5-QU |

Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5-1000-00A(H) |

Dane biznesowe

| | |
|---|---|
| numer zamówienia | 11040000076 |
| Jednostka opakowania | 100 |
| Minimalna ilość zamówienia | 100 |
| Waga produktów (bez opakowania) | 6.113 |