Überblick

Informationen zum Produkt



DSW-A8K0008-30090000002

8 110/100Mbs BaseT port, IP30Operating temperature-40°C~+75°C.12/24/48 VDC & 24VAC (9.6~60 VDC & 18~30 VAC) power supply enter(Only connect to class 2 power).

Produktvorteile

☑Unmanaged Industrial Switch made from Anti-Corrosion Aluminum Alloy.
☑8 10/100BaseT Ports.
☑12/24/48 VDC & 24VAC (9.6~60VDC & 18~30 VAC) Power Input
☑Operating Temperature from -40°C to +75°C.
☑IP30 Protection Class

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

interface

Port 1 Type	RJ45
Number of ports 1	8
Transmission rate	10/100 Mbps

Mechanical structure

Shell material	Die-cast aluminum alloy housing
switch	QoS function, BSP (Broadcast Storm Protection) function
Installation method	Card rail installation
Protection class	IP30

exchange property	
MAC table size	4K
Bandwidth backplane	16Gbps
packet buffer	1.5Mb
MTBF	
Standards compliant	Telcordia SR-332
operating hours	≥38,7641H
Warranty	
Warranty	5 years
power supply	
Supply voltage range	9.6~60VDC & 18~30VAC
reverse voltage protection	support
Connection Type	2P plug-in terminal
connecting wire diameter	0.5~1.5mm/ 28~16AWG
Overcurrent protection	support
Input voltage	12/24/48 VDC & 24 VAC
Dimension	
high	100mm
length	61.8mm
width	40mm
Environmental data	
working altitude	≤2000m
Operating temperature	-40°C~+75°C
storage temperature	-40°C~+85°C
humidity	5% ~ 95% (non-condensing)

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	30090000002
Verpackung Einheit	1 STK
Minimale Bestellmenge	1 STK
Produktgewicht (ohne Verpackung)	230g