
## Przegląd

### Informacje o produkcie



# DS4-MT-11040000213

Disconnect terminal blocks, connector method: Push-in connector, Rated voltage : 500 V,Rated current : 20 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 6 mm², AWG: 24 - 10, Width: 6.2 mm, Color: gray, Mounting type: NS35/7.5, NS35/15

### Zalety produktu

☑Disconnect terminal blocks.
☑Push-in connection technology, tool-free operation, more convenient and faster;
☑With orange wire button, one word or cross screwdriver can release wire.
☑The circuit can be disconnected, measured, controlled easily by operate the knife disconnector.
☑Equipped with test holes on both sides of the breaking point, convenient for testing the circuit.
☑Snap-on knife disconnector to prevent accidental disconnection.
☑Universal breaking area to achieve different functions, can insert breaking plug, component plug, fuse plug.

### Certyfikacja produktu

## Dane techniczne

### Rysunek produktu

### Model 3D

### Wiring data

| | |
|---|---|
| Strip length | 11~13mm |
| Conductor cross section solid | 0.2~6mm² |
| Conductor cross section flexible | 0.2~4mm² |
| Conductor cross section solid AWG | 24~10 |

### Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |

| | |
|---|---|
| Relative humidity (storage/transport) | 25%~75% |

IEC Electrical parameters

| | |
|---|---|
| Rated voltage (III / 3) | 500V |
| Rated surge voltage | 6KV |

Environmental protection

| | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

Dimension

| | |
|---|---|
| NS 35/7,5 Height | 36.8mm |
| End plate width | 1.5mm |
| NS 35/15 Height | 44.3mm |
| length | 55.6mm |
| width | 6.2mm |

Overview

| | |
|---|---|
| Connection type | In line connection |
| Number of rows | 1 |
| number of connections | 2 |
| Open-end side panels | Yes |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

## Akcesoria

Marker

| | |
|---|---|
| Top marker | / |
| Side marker | ZSF6 |

| | |
|---|---|
| Marker support | / |

Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) mm | 0.6x3.5 |
| Bridge | DFBXX-6.2 |
| End cover | D-DS4-HE |

Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5-1000-00A(H) |

Dane biznesowe

| | |
|---|---|
| numer zamówienia | 11040000213 |
| Jednostka opakowania | 100 |
| Minimalna ilość zamówienia | 100 |
| Waga produktów (bez opakowania) | 9.3 |