Przegląd

Informacje o produkcie



DS4-HE-LD250-11040000164

Fuse terminal blocks, connector method: Push-in connector, Fuse type: G / 5 x 20, Glass/ceramic/..., Rated voltage : 250 V,Rated current : 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 6 mm², AWG: 24 - 10, Width: 6.2 mm, Color: black, Mounting type: NS35/7.5, NS35/15

Zalety produktu

☑Fuse terminal blocks.
☑Push-in connection technology, tool-free operation, more convenient and faster;
☑With orange wire button, one word or cross screwdriver can release wire.
☑Snap-on fuse box for easy fuse replacement.
☑Equipped with LED indicator for quick identification of fusing status.
☑Equipped with dual-channel bridge wells, circuit connection testing is more flexible.
☑Equipped with test holes for easy testing of the circuit.

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

Wiring data

Strip length	11~13mm
Conductor cross section solid	0.2~6mm²
Conductor cross section flexible	0.2~4mm²
Conductor cross section solid AWG	24~10

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）

Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	250V
Rated current (III / 3)	6.3A

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	36.8mm
End plate width	1.5mm
NS 35/15 Height	44.3mm
length	55.6mm
width	6.2mm

Overview

Connection type	In line connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
fuse	G/5 x 20
Fuse type	Glass/ceramic/...

Akcesoria

Marker

Top marker	ZB6 / ZS6
Side marker	ZSF6
Marker support	DTH5-25x5 / DTH5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5
Bridge	DFBXX-6.2
End cover	D-DS4-HE

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Dane biznesowe

numer zamówienia	11040000164
Jednostka opakowania	100
Minimalna ilość zamówienia	100
Waga produktów (bez opakowania)	9.705