
DEGSON

## Überblick

### Informationen zum Produkt



15EDGA-3.5-10020000001

Pluggable terminal blocks,Rated current:7A.Rated voltage （III/2）:250V,pitch:3.5mm,Color:green,Contact surface :Tin

### Produktvorteile

☑ PCB welding, plug direction is parallel to the PCB
☑ Multiple contacts to provide touch protection for connection

### Zertifizierung von Produkten

c UL us

## Technische Daten

### Produktzeichnung

### 3D-Modell

### Processing notes

| | |
|---|---|
| Process | Wave soldering/manual soldering |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated current (B) | 8A |

### Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 250V |
| Rated voltage(III/3) | 160V |
| Rated current | 7A |
| Rated voltage(III/2) | 250V |

| | |
|---|---|
| Rated voltage(II/2) | 320V |
| Rated surge voltage(III/3) | 2.5KV |
| Rated surge voltage(III/2) | 2.5KV |
| Rated surge voltage(II/2) | 2.5KV |

Item properties

| | |
|---|---|
| Connection direction | 0° |
| Type of installation | PCB welding |
| Pin arrangement | Double-row in a straight line |
| Pitch | 3.5mm |
| Number of potentials | 2 |
| Pluggable or not | Yes |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | Ⅰ |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

Zubehör

## Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

## Tool

| | |
|---|---|
| Operating tool | / |
| Screwdriver | / |

## Die Geschäftsdaten

| | |
|---|---|
| Nummer der Bestellung | 10020000001 |
| Verpackung Einheit | 3575 |
| Minimale Bestellmenge | |
| Produktgewicht (ohne Verpackung) | 0.6 |