
Überblick

Informationen zum Produkt



2EDG-STD-5.0-10010002817

Pluggable terminal blocks,Rated current:24A.Rated voltage（III/2）:250V,pitch:5.0mm,Color:green,Contact surface :Tin

Produktvorteile

☑ Adapt to multi-type plugs, device design is highly flexible
☑ Keying requirements can be met
☑ Panel mounting, suitable for various situations

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

Conductor cross section solid	1.0~2.5mm²
Conductor cross section flexible	1.0~2.5mm²
AWG	28~12AWG
Torque	0.4N.m
Strip length	8mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	250V
Rated current	24A
Rated voltage(III/2)	250V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	0°
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2.5
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0

Mechanical tests	
Test Specification	IEC61984/ UL1059

Environmental data	
Ambient temperature (operation)	-40℃~105℃

Zubehör

Tool	
Screwdriver	0.6x3.5，Slotted screwdriver
Operating tool	/

Accessories	
Coding strip	2EDG-PWI
Bridge	/
Marking strip	/
Others	/

Die Geschäftsdaten

Nummer der Bestellung	10010002817
Verpackung Einheit	100
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	4.33