Overview

Product information



DGR500-00A(H)-12010000272

Transfer barrier terminal blocks,Rated current:500A.Rated voltage（UL）:600V,Cross section:300~750kcmil,pitch:60mm,Color:black,Contact surface:Tin

Product advantages

☑ Screw connection for worldwide use
☑ Fence type wiring structure, stable and reliable connection
☑ Provide the cabinet and panel electrical transfer connections

Product certification

CE

Technical data

Product drawing

3D model

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	500A
Rated current (C)	500A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line

Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M16
Pitch	60mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059

Environmental data

Ambient temperature (operation)	-40℃~125℃(depending on derating curve)

Accessories

Accessories

Business data

Order number	12010000272

Packing unit	1
Minimum order quantity	/
Products weight (without packaging)	1400