
## Überblick

### Informationen zum Produkt



# 5EDGK-7.62-10010002899

Pluggable terminal blocks,Rated current:32A.Rated voltage （III/2）:400V,pitch:7.62mm,Color:green,Contact surface :Tin

### Produktvorteile

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying parts can be installed
☑ Universal installation method, suitable for various situations

### Zertifizierung von Produkten

## Technische Daten

### Produktzeichnung

### 3D-Modell

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.2~4mm² |
| Conductor cross section flexible | 0.2~4.0mm² |
| AWG | 30~10AWG |
| Torque | 0.5N.m |
| Strip length | 7mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (C) | 300V |
| Rated voltage (D) | 300V |

| | |
|---|---|
| Rated current (B) | 30A |
| Rated current (D) | 10A |
| Rated current (C) | 30A |

Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 400V |
| Rated current | 32A |
| Rated voltage(III/2) | 400V |
| Rated surge voltage(III/2) | 4KV |

Item properties

| | |
|---|---|
| Connection direction | 0° |
| Screwdriver | Slotted screwdriver |
| screw thread | M3 |
| Pitch | 7.62mm |
| Number of potentials | 2 |
| Pluggable or not | Yes |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact point metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

### Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## Zubehör

### Tool

| | |
|---|---|
| Screwdriver | / |
| Operating tool | / |

### Accessories

| | |
|---|---|
| Coding strip | 5EDG-PWI |
| Bridge | / |
| Marking strip | / |
| Others | / |

## Die Geschäftsdaten

| | |
|---|---|
| Nummer der Bestellung | 10010002899 |
| Verpackung Einheit | 50 |
| Minimale Bestellmenge | |
| Produktgewicht (ohne Verpackung) | 5.71 |