
Overview

Product information



Relay module-DM108-RM-32-PN-2-4M-01A(H)-30030000048

ordinary Relay Module,with 40P/20P Horn connector,with relay Socket ,can install 32 ordinary relays,with 1C/O,with indicator light,Omron relay,PNP or NPN signal can be input (Please contact us for relay replacement)

Product advantages

☑ Each signal channel and power supply voltage have LED status indicators
☑ Pluggable ordinary relay, with 1C/O changeover contact, one-to-one output at the output terminal
☑ Suitable for NPN, PNP controller
☑ Freewheeling diode for each signal path
☑ Prefabricated cables, plug and play, fast wiring

Product certification

Technical data

Product drawing

3D model

Overview

Installation location	Arbitrary
Number of channels	32
Shell Insulation Materials	PVC/PA66
color	green

Dimension

width	125mm
Height	70mm
length	186mm

Enter technical data

Rated input voltage	24VDC
Input voltage range relative to UN	0.9....1.1
protected name	Polarity protection
Protection circuits/components	Polarity Protection Diode
Status display/channel	green

Export technical data

contact type	1C/O
Maximum switching voltage	240VAC 30VDC
Limit continuous current	16A
Fault monitoring (open circuit/short circuit)	no

Output connection data

connection name	output
Connection method	screw connection
Stripping length	6-7mm
thread	M3
connection volume	32
number of digits	3
Hard conductor cross section	1.0 ... 2.5mm²
Flexible conductor cross section	1.0 ... 2.5mm²
Connectable guide cross section AWG	28...12AWG

Enter connection data

connection name	enter
Connection method	IDC/MIL connectors
connection volume	1

number of digits	40

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Accessories

Business data

Order number	30030000048
Packing unit	3
Minimum order quantity	3
Products weight (without packaging)	360