Überblick

Informationen zum Produkt



10A-GF-0.37-92116900108

10A silver gold female pins,Adapter wire specification0.37mm²

Produktvorteile

☑High-precision turning process, stable and reliable products;
☑Gold-plated and silver-plated are available, suitable for different environmental requirements;
☑Comprehensive products, resistant to temperature changes, shocks and harsh environments。

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

Marking

classification	Contact
Series	10A
Contact type	Crimping contact

versions

Female/Male	Female
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Material	Copper alloy
Plating material	Gold plate

Standards

Connection meets standards	EN 60664-1 IEC 61984

Technical specification

Conductor cross sections（mm²）	0.37mm²
Conductor cross sections(AWG)	22AWG
Working current	≤10A
Contact resistance	≤3mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	8mm
working life-mating cycles	≥500

Zubehör

Die Geschäftsdaten

Nummer der Bestellung	92116900108
Verpackung Einheit	
Minimale Bestellmenge	100
Produktgewicht (ohne Verpackung)	0.6592