Overview

Product information



Interface module-DT011-00A(H)-30040000082

32 positions input output module,with indicator light,with screw connector and IDC stitching line,can access 32 positions NPN/PNP signal,can be installed on DIN35 rail

Product advantages

Suitable for 32-point (34/40-bit interface) controller， Screw connection

Product certification

Technical data

Product drawing

3D model

Dimension

width	57mm
Height	43mm
length	111mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	32
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	40
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm² ... 2.5 mm²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	34
screw thread	M3
Hard wire cross section	1.0 mm² ... 2.5 mm²

Accessories

Accessories

Wire harness	DX210-4S-500-00A(H)

Business data

Order number	30040000082
Packing unit	1
Minimum order quantity	10
Products weight (without packaging)	128