Overview

Product information



Relay Socket-DPTF-08A-3-00A(H)-30020000053

DPTF Relay Socket, used for 2PDT relays, screw connections

Product advantages

- ☑ Screw base relay socket
- ☑ Safe isolation between coil and contacts
- ☑ 10A ,2PDT

Product certification

Technical data

Product drawing

3D model

Dimension

width	30mm
length	71mm
Depth including bracket	27.5mm

Environmental data

Ambient temperature (operation)	-45℃～+85℃
Ambient temperature (storage / transport)	-40℃~+65℃

Technical data

Rated voltage UN	300V

Installation location	Arbitrary
Assembly instructions	DIN35 rail
Maximum allowable current	10A

Connection data 1

Connection name	enter
Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5-2.5mm²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5-2.5mm²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Accessories

Business data

Order number	30020000053
Packing unit	10 SKT
Minimum order quantity	10 SKT
Products weight (without packaging)	45g