
Overview

Product information



DVMN-006-MC-21020000498

Combination module plug, 6-core, male plug, cold press connection

Product advantages

☑ Cold press connection technology, suitable for a wide range of wire specifications
☑ Modular products for easy assembly and maintenance

Product certification

Technical data

Product drawing

3D model

Versions

Dimension	1 module
Number of positions	6
Connection method	Crimping connection
Female/Male	Male
PE Contacts	No

Marking

classification	Insert
Series	DM

Material characteristics

Material（insert）	Polycarbonate（PC）

Materia（Contact）	Copper alloy
Surface（Contact）	Silver plated
Flammability rating	V-0
color	Grey/White（RAL 7032）
RoHS	Comply with RoHS exemptions

Electrical parameters

Pollution level	3
Rated current	16A
	830V
Rated pulse voltage	8KV
On the basis of UL /CSARated current	600V
Insulation resistance	≥10^10Ω
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	7.5mm
Conductor cross sections（mm²）	0.14-4.0mm²
Conductor cross sections(AWG)	26-12AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984

Accessories

Business data

Order number	21020000498

Packing unit	1
Minimum order quantity	1
Products weight (without packaging)	11.7