
Overview

Product information



DG270-10.0-10060001398

PCB spring terminal blocks,Rated current:76A.Rated voltage （III/2）:400V,pitch:10.0mm,Color:green,Contact surface :Tin

Product advantages

☑ Cage clamp connection technology,fast wiring
☑ Universal installation method, suitable for various situations
☑ Rotatable operating handle,easy to operate

Product certification

Technical data

Product drawing

3D model

Electrical parameters IEC

Rated voltage	400V
Rated voltage(III/3)	400V
Rated current	76A
Rated voltage(III/2)	400V
Rated voltage(II/2)	800V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	0°

Pitch	10mm
Number of potentials	4
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Insulation Materials	PA66
Insulating material group	Ⅰ
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10060001398
Packing unit	0
Minimum order quantity	30
Products weight (without packaging)	10.15