
DEGSON

## Overview

### Product information



# DG264-10.0-10060002566

PCB spring terminal blocks,Rated current:76A.Rated voltage（III/2）:320V,pitch:10.0mm,Color:gray,Contact surface :Tin

### Product advantages

☑ Universal installation method, suitable for various situations
☑ 45°connection can realize multi-row layout on PCB
☑ Different poles can be combined through the side lock

### Product certification

c UL us

## Technical data

### Product drawing

### 3D model

### Processing notes

| | |
|---|---|
| Process | Wave soldering/manual soldering |

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.2~16mm² |
| Conductor cross section flexible | 0.2~16mm² |
| AWG | 24~4AWG |
| Strip length | 12mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (C) | 300V |

| | |
|---|---|
| Rated voltage (D) | 300V |
| Rated current (B) | 66A |
| Rated current (D) | 10A |
| Rated current (C) | 66A |

Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 320V |
| Rated voltage(III/3) | 320V |
| Rated current | 76A |
| Rated voltage(III/2) | 320V |
| Rated voltage(II/2) | 630V |
| Rated surge voltage(III/3) | 4KV |
| Rated surge voltage(III/2) | 4KV |
| Rated surge voltage(II/2) | 4KV |

Item properties

| | |
|---|---|
| Connection direction | 45° |
| Type of installation | PCB welding |
| Pin arrangement | Double-row in a straight line |
| Connection method | spring-cage connection |
| Pitch | 10mm |
| Number of potentials | 5 |
| Pluggable or not | no |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |

| | |
|---|---|
| Contact material | copper |
| Contact point metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | IEC60947/UL1059 |

Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃(depending on derating curve) |

## Accessories

Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

Tool

| | |
|---|---|
| Operating tool | / |
| Screwdriver | / |

## Business data

| | |
|---|---|
| Order number | 10060002566 |
| Packing unit | 45 |
| Minimum order quantity | 30 |
| Products weight (without packaging) | 34.35 |