종람

제품 장점



9EDGK-7.5-10020001573

Pluggable terminal blocks,Rated current:20A.Rated voltage（III/2）:630V,pitch:7.5mm,Color:black,Contact surface :Tin

제품 장점

☑ Cage clamp pluggable connection technology,reliable wiring
☑ Self-locking structure with sound prompt,safe to use

제품 인증

기술 데이터

제품 도면

3D

Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	28~12AWG
Strip length	8mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	600V
Rated current (B)	16A

Rated current (D)	5A
Rated current (C)	16A

Electrical parameters IEC

Rated voltage	630V
Rated voltage(III/3)	500V
Rated current	20A
Rated voltage(III/2)	630V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	0°
Connection method	spring-cage connection
Pitch	7.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	Gold plate
Insulation Materials	PA66
Insulating material group	II

Flammability rating	UL94V-0

Mechanical tests	
Test Specification	IEC61984/ UL1059

Environmental data	
Ambient temperature (operation)	-40℃~105℃

악세사리

Tool	
Screwdriver	/
Operating tool	DG010

Accessories	
Coding strip	/
Bridge	DG018-7.5
Marking strip	/
Others	/

비즈니스 데이터

발주 번호	10020001573
포장 단위	100
MOQ	30
제품 무게 (포장 제외)	4.402