종람

제품 장점



DG38R-B-12040000409

Single-layer PCB barrier terminal blocks,Rated current:15A.Rated voltage（UL）:300V,Cross section:22-14AWG,pitch:8.25mm,Color:black,Contact surface :Tin

제품 장점

☑ Screw connection for worldwide use
☑ Fence type wiring structure, stable and reliable connection
☑ Solder plate mounting for electrical connection of the device to the PCB

제품 인증

기술 데이터

제품 도면

3D

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

AWG	22~14AWG
Torque	0.5N.m

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	150V
Rated voltage (D)	300V

Rated current (B)	15A
Rated current (D)	10A
Rated current (C)	15A

Electrical parameters IEC

Rated current	
	24A

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3
Pitch	8.25mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	II
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059

Environmental data	
Ambient temperature (operation)	-40℃~105℃

악세사리

Accessories	

비즈니스 데이터

발주 번호	12040000409
포장 단위	495
MOQ	/
제품 무게 (포장 제외)	4.9