종람

제품 장점



5CDG-7.62-10020000913

Pluggable Terminal Blocksnominal current32A.Rated voltage(Ⅲ/2)：400V,pitch:7.62mm,Color:green,Contact surface:Tin

제품 장점

☑ Adapt to multi-type plugs, device design is highly flexible
☑ Through-wall installation, free positioning

제품 인증

기술 데이터

제품 도면

3D

Packaging information

Type of packaging	box-packed

Electrical parameters UL

Rated voltage (C)	300V
Rated current (B)	30A
Rated current (C)	30A

Electrical parameters IEC

Rated voltage	400V
Rated current	32A
Rated voltage(Ⅲ/2)	400V

Rated surge voltage(III/2)	4KV

Item properties

Connection direction	0°
Type of installation	panel
Pin arrangement	Single row in a straight line
Pitch	7.62mm
Number of potentials	3
Pluggable or not	Yes
Number of rows	1

Material data

Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PBT
Relative tracking index CTI	250V
Glow Wire Flammability Index GWFI	850
Shell color	green
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984

Environmental data

Ambient temperature (operation)	-40℃~105℃

악세사리

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

비즈니스 데이터

발주 번호	10020000913
포장 단위	
MOQ	
제품 무게 (포장 제외)	