종람

제품 장점



## DSW-A8K0008-30090000002

8 110/100Mbs BaseT port, IP30Operating temperature-40°C~+75°C.12/24/48 VDC & 24VAC (9.6~60 VDC & 18~30 VAC) power supply enter(Only connect to class 2 power).

제품 장점

☑Unmanaged Industrial Switch made from Anti-Corrosion Aluminum Alloy.
☑8 10/100BaseT Ports.
☑12/24/48 VDC & 24VAC (9.6~60VDC & 18~30 VAC) Power Input
☑Operating Temperature from -40°C to +75°C.
☑IP30 Protection Class

제품 인증

기술 데이터

제품 도면

3D

interface

| | |
|---|---|
| Port 1 Type | RJ45 |
| Number of ports 1 | 8 |
| Transmission rate | 10/100 Mbps |

Mechanical structure

| | |
|---|---|
| Shell material | Die-cast aluminum alloy housing |
| switch | QoS function, BSP (Broadcast Storm Protection) function |
| Installation method | Card rail installation |
| Protection class | IP30 |

| exchange property | |
|---|---|
| MAC table size | 4K |
| Bandwidth backplane | 16Gbps |
| packet buffer | 1.5Mb |
| **MTBF** | |
| Standards compliant | Telcordia SR-332 |
| operating hours | ≥38,7641H |
| **Warranty** | |
| Warranty | 5 years |
| **power supply** | |
| Supply voltage range | 9.6~60VDC & 18~30VAC |
| reverse voltage protection | support |
| Connection Type | 2P plug-in terminal |
| connecting wire diameter | 0.5~1.5mm/ 28~16AWG |
| Overcurrent protection | support |
| Input voltage | 12/24/48 VDC & 24 VAC |
| **Environmental data** | |
| working altitude | ≤2000m |
| Operating temperature | -40°C~+75°C |
| storage temperature | -40°C~+85°C |
| humidity | 5% ~ 95% (non-condensing) |
| **Dimension** | |
| high | 100mm |
| length | 61.8mm |
| width | 40mm |

## 악세사리

## 비즈니스 데이터

| | |
|---|---|
| 발주 번호 | 30090000002 |
| 포장 단위 | 1 STK |
| MOQ | 1 STK |
| 제품 무게 (포장 제외) | 230g |