Aperçu

informations sur le produit



MIL cable-DX210-1S-500-00A(H)-23040000005

MIL cable,connector1:IDC/MIL female connector（1×10 Core,180° output）,connector2:IDC/MIL female connector（1×10 Core,180° output）

Les avantages des produits

☑The cable is soft and has good bending resistance
☑Prefabricated connector, beautiful appearance
☑ Provide single-ended and double-ended cables
☑ Save wiring time, and can achieve fast wiring with the company's interface module

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

Environmental data

Ambient temperature (operation)	-20 °C ... 80 °C
Ambient temperature (storage / transport)	-20 °C ... 80 °C

Standards/Regulations

Flame retardant	ULVW-1
Oil resistance	Oil resistant
Gasoline resistance	≤246Ω/KM
Connection meets standards	UL758

Technical data

Maximum allowable working voltage	30VDC

Maximum current carrying capacity of each path	0.7A
cable length	0.5米
Cable outer diameter	5.0mm
Single strand, cross-sectional area	0.08mm²
Single strand, cross section (AWG)	28

Connection data 1

Connection name	Control system side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	10
spacing	2.54mm
Exit angle	180°

Connection data 2

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	10
Exit angle	180°
spacing	2.54mm

Overview

Single wire, number of twisted wires	10
Single stranded wire, material	Tinned copper
shield	Yes
Outer sheath, material	PVC
Outer sheath,color	black

Accessoires

Caractéristiques commerciales

Numéro de la commande	23040000005
Unité d'emballage	1
Quantité minimale de commande	10
Le poid de produit (sans emballage)	50