DEGSON

Aperçu

informations sur le produit



DG69-A-12050000034

Transfer barrier terminal blocks,Rated current:25A.Rated voltage（UL）:300V,Cross section:22~12AWG,pitch:11.00mm,Color:black,Contact surface:Tin

Les avantages des produits

☑ Screw connection for worldwide use
☑ Fence type wiring structure, stable and reliable connection
☑ Panel mounting for electrical transfer between two devices in a small space

Les certificates des produits

c UL us CE

Caractéristiques techniques

Dessin de produit

Modèle 3D

Connection capacity

AWG	22~12AWG
Torque	0.8N.m

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	300V
Rated current (B)	25A
Rated current (D)	10A

Rated current (C)	25A

Electrical parameters IEC

Rated current	
	32A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3.5
Pitch	11mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059

Environmental data

Ambient temperature (operation)	-40℃~125℃

Accessoires

Accessories

Caractéristiques commerciales

Numéro de la commande	12050000034
Unité d'emballage	300
Quantité minimale de commande	/
Le poid de produit (sans emballage)	13.3