
## Aperçu

### informations sur le produit



# 2EDGKC-5.0-10010002135

Pluggable terminal blocks,Rated current:20A.Rated voltage （III/2）:320V,pitch:5.0mm,Color:green,Contact surface :Tin

### Les avantages des produits

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying requirements can be met
☑ Universal installation method, suitable for various situations

### Les certificates des produits

## Caractéristiques techniques

### Dessin de produit

### Modèle 3D

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.2~2.5mm² |
| Conductor cross section flexible | 0.2~2.5mm² |
| AWG | 28~12AWG |
| Torque | 0.5N.m |
| Strip length | 10mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (C) | 150V |
| Rated voltage (D) | 300V |

| | |
|---|---|
| Rated current (B) | 15A |
| Rated current (D) | 10A |
| Rated current (C) | 15A |

Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 320V |
| Rated current | 20A |
| Rated voltage(III/2) | 320V |
| Rated surge voltage(III/2) | 4KV |

Item properties

| | |
|---|---|
| Connection direction | 90° |
| Connection method | Screw connection |
| Screwdriver | Slotted screwdriver |
| screw thread | M2.5 |
| Pitch | 5mm |
| Number of potentials | 4 |
| Pluggable or not | Yes |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact point metal surface | tin-plated |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

| Mechanical tests | |
|---|---|
| Test Specification | IEC61984/ UL1059 |
| **Environmental data** | |
| Ambient temperature (operation) | -40℃~105℃ |

## Accessoires

| Tool | |
|---|---|
| Screwdriver | 0.6x3.5，Slotted screwdriver |
| Operating tool | / |
| **Accessories** | |
| Coding strip | 2EDG-PWI |
| Bridge | DG019-5.0 |
| Marking strip | / |
| Others | / |

## Caractéristiques commerciales

| | |
|---|---|
| Numéro de la commande | 10010002135 |
| Unité d'emballage | 490 |
| Quantité minimale de commande | |
| Le poid de produit (sans emballage) | 11.589 |