Aperçu

informations sur le produit



FCN cable-DX215-10S-500-00A(H)-23040000046

FCN cable,connector1:FCN female connector（1×40 Core,90° output）,connector2:IDC/MIL female connector（1×40 Core,90° output）

Les avantages des produits

☑The cable is soft and has good bending resistance
☑Prefabricated connector, beautiful appearance
☑ Provide single-ended and double-ended cables
☑ Applicable to Omron CJ1 series PLC
☑ Save wiring time, and can achieve fast wiring with the company's interface module

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

Environmental data

Ambient temperature (operation)	-20 °C ... 80 °C
Ambient temperature (storage / transport)	-20 °C ... 80 °C

Standards/Regulations

Flame retardant	ULVW-1
Oil resistance	Oil resistant
Gasoline resistance	≤246Ω/KM
Connection meets standards	UL758

Technical data

Maximum allowable working voltage	30VDC
Maximum current carrying capacity of each path	0.7A
cable length	0.5米
Cable outer diameter	6.5mm
Single strand, cross-sectional area	0.08mm²
Single strand, cross section (AWG)	28

Connection data 1

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	40
spacing	2.54mm
Exit angle	90°

Connection data 2

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	40
Exit angle	90°
spacing	2.54mm

Overview

Single wire, number of twisted wires	40
Single stranded wire, material	Tinned copper
shield	Yes
Outer sheath, material	PVC

Outer sheath,color	black

Accessoires

Caractéristiques commerciales

Numéro de la commande	23040000046
Unité d'emballage	1
Quantité minimale de commande	10
Le poid de produit (sans emballage)	50