Overview

Product information



PCSH-M23R-12P-MM-SL7001-00A(H)-20050000012

Motor connector, M23 × 1-pin on-site assembly plug, straight head, shielded. Rated voltage: 630V, rated current: 28 A, connection method: crimping type, contact type: pin type

Product advantages

☑ Cross manufacturer compatibility and global universality.
☑ Multiple combination methods to meet various installation environments.
☑ 360 ° full shielding, suitable for complex electromagnetic interference and other environments.
☑ Optimize the structure. Improve the locking of the end of the line to reduce potential faults; Innovate anti backflow needles to prevent internal structural looseness; Secondary fastening improves product reliability.
☑ It has seismic resistance and can ensure high reliability of the product even in harsh environments.
☑ Easy to install, even non professionals can quickly assemble and replace defective parts.
☑ The test report is complete.

Product certification

RoHS

Technical data

Product drawing

3D model

Overview

shield	Yes

Environment condition

Ambient temperature (operation)	-40°C ~ +125°C

Technical parameter

Withstand voltage	2000V AC

General parameters

Rated current	8A
	160V
Number of potentials	12
Insulation resistance	≥ 100 MΩ

Technical specification

IP class	IP67

Accessories

Business data

Order number	20050000012
Packing unit	10
Minimum order quantity	/
Products weight (without packaging)	/