
Visión general

Información del Producto



Bus IO-DF750-200-11-2001A(H)-30050000139

Card type IO shell,8 channel input output module Housing,with LED display,golden finger connector Disconnect all

Ventajas del producto

☑ Free-hand plugging and unplugging, easy to assemble
☑ Internal bus through 6 gold-plated terminals at the bottom
☑ Equipped with 8 channels function module, each node is equipped with LED
☑ Two internal gold-plated blade connectors are used for power cascade expansion
☑ Can be installed on DIN rail

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

Dimension

length	100mm
width	12mm (main module)
Height	66.8mm

Mechanical parameters

structure type	Compact terminal module housing with signal LED
Material	PC+PA66
installation	DIN35 rail
Side by side installation	Dovetail groove clamping
label	Laser screen printing

color	C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Connection method(IO)

wiring	Spring type wiring technology
Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Accesorios

Accessories

IO housing	DF750-001-11-2001A(H)

Datos empresariales

Número de pedido	30050000139
Unidad de embalaje	200
Cantidad mínima de pedido	200
Peso del producto (sin embalaje)	40