Visión general

Información del Producto



Bus IO-DF750-002-11-2001A(H)-30050000130

Card type IO shell,can be equipped with RJ45 connector,LED indicator

Ventajas del producto

☑ Dual network port with light RJ45 interface
☑ 8-bit address interface
☑ Internal bus through 6 gold-plated terminals at the bottom
☑ Equipped with 8 channels power module, each node is equipped with LED
☑ Two internal gold-plated blade connectors are used for power cascade expansion
☑ Can be installed on DIN rail

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

Dimension

length	93.5mm
width	48mm
Height	69mm

Mechanical parameters

structure type	Compact terminal module housing with signal LED
Material	PC+PA66
installation	DIN35 rail
Side by side installation	Dovetail groove clamping

label	Laser screen printing
color	C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Connection method(IO)

wiring	Spring type wiring technology
Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Accesorios

Accessories

IO housing	DF750-200-11-2001A(H)

Datos empresariales

Número de pedido	30050000130
Unidad de embalaje	20
Cantidad mínima de pedido	20
Peso del producto (sin embalaje)	122.5