종람

제품 장점



## PCMT4-11010000145

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 800 V,Rated current: 16 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 4 mm², AWG: 24 - 12, Width: 6.2 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

제품 장점

☑Disconnect terminal blocks；
☑Screw connection technology, reliable connection；
☑Copper alloy material, good corrosion resistance；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

제품 인증

CE

기술 데이터

제품 도면

3D

Wiring data

| | |
|---|---|
| Screw type | Slotted screw |
| 2 flexible conductors with a TWIN ferrule | 0.5-1.5mm² |
| Strip length | 10~11mm |
| Conductor cross section solid | 0.2~4mm² |
| Conductor cross section flexible | 0.2~4mm² |
| Conductor cross section solid AWG | 24~12 |
| screw thread | M3 |
| Tightening torque | 0.5N.m |

## Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |

## IEC Electrical parameters

| | |
|---|---|
| Rated voltage (III / 3) | 800V |
| Rated current (III / 3) | 16A |
| Rated surge voltage | 8KV |

## Environmental protection

| | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

## Dimension

| | |
|---|---|
| NS 35/7,5 Height | 47.4mm |
| NS 35/15 Height | 54.9mm |
| length | 51mm |
| width | 6.2mm |
| Height | 46mm |

## Overview

| | |
|---|---|
| Connection method | screw connection |
| Number of rows | 1 |
| number of connections | 2 |
| Open-end side panels | no |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

악세사리

## Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) | 0.6×3.5 |
| Fixed bridge | / |
| Insertion bridge | EB2-6 / EB3-6 / EB10-6 / EBA40-6 |
| End cover | / |
| Separating disk | / |
| Partition plate | / |

## Marker

| | |
|---|---|
| Top marker | / |
| Marker | ZB6 |
| Marker support | / |

## Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5 & NS35/15 |

## Marking & Installation

| | |
|---|---|
| Marking strip | ZB6 |
| Marker cards | DBE-1 |

## Accessories

| | |
|---|---|
| Bridge | EBXX-6 |
| End clamp | E-WS |
| DIN rail | NS35/7.5-1000-00A(H) |

## 비즈니스 데이터

| | |
|---|---|
| 발주 번호 | 11010000145 |

| | |
|---|---|
| 포장 단위 | 100 |
| MOQ | 100 |
| 제품 무게 (포장 제외) | 12.689 |