Aperçu

informations sur le produit



RM-EBBH-2006-M-1000-00A(H)-25080000001

Charging and discharging plug at the end of electric motorcycle battery, with rated current of 100A~120A; Rated voltage 72V DC; Withstand voltage 1500V AC; Insulation resistance ＞ 500M Ω; Protection grade: IP67 when mated; Mechanical life ≥ 3000 times; Pull out force ＞20N; Working temperature: - 40 ~ 105 ℃; Salt spray resistance for 72h; Flame retardant grade ul94-v0; Environmental protection:RoHS

Les avantages des produits

☑ Compact structure and high space utilization
☑ Adopt bayonet locking structure to prevent accidental unlocking
☑ Direct plug operation, convenient and fast
☑ Signal pin No.：0~8 pins
☑ Multiple auditory and visual feedback are inserted in place
☑ Beautiful appearance, fit human functional design

Les certificates des produits

RoHS

Caractéristiques techniques

Dessin de produit

Modèle 3D

Marking

Series	DA
	DD
	DF

versions

Connection method	Crimping connection
Female/Male	Male

Dimension	3A
	32A
	6B
	10B
	24B
	32B
	48B
Number of positions	15
	25
	32
	42

Paramètre technique

Résistance d'isolement	≥500MΩ
Vie mécanique	≥3000次

Paramètres environnementaux

Classe de protection	MatchingIP67

Accessoires

Caractéristiques commerciales

Numéro de la commande	25080000001
Unité d'emballage	
Quantité minimale de commande	
Le poid de produit (sans emballage)	